SPL-150



SPECIFICATIONS	
FREQUENCY RESPONSE	18Hz - 125Hz
MAXIMUM ACOUSTIC OUTPUT	122dB
AMPLIFIER TYPE	All digital
AMPLIFIER POWER	400W / 800W
WOOFER	15" (38.1 cm) long-throw copper spun cerametallic, front-firing woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex
INPUTS	L/R line-level/LFE RCA jacks, Wireless WA-2 Port
HEIGHT	21.5" / 54.61 cm
WIDTH	19.5" / 49.53 cm
DEPTH	22.3" / 56.64 cm
WEIGHT	75.4 lbs / 34.2 kg
FINISH	Ebony Vinyl
BUILT FROM	2018

A STEP-UP FROM OUR REFERENCE SERIES SUBWOOFERS, THE SPL SERIES HAVE BEST-IN-CLASS MAXIMUM OUTPUT LEVELS MAKING THEM HIGH-PERFORMANCE SUBWOOFERS AT AFFORDABLE PRICES.

SPUN COPPER FRONT-FIRING CERAMETALLIC WOOFERS
Cerametallic™ woofers are exceptionally light and extremely rigid, providing remarkable low frequency response with minimal cone breakup and distortion for higher, cleaner output using less amplifier power.

HIGH EFFICIENCY CLASS D AMPLIFIER
The built-in, high efficiency amplifier features an analog preamp design, which maintains the original signal path for cleaner, true-to-source reproduction. The Class D output stage ensures maximum efficiency for maximum output, detail, and low frequency power.

FRONT-FIRING SLOT PORT WITH EXCLUSIVE INTERNAL FLARE TECHNOLOGY
Proprietary internal geometry that minimizes port noise for clean undistorted low frequencies. The front-firing design allows for placement flexibility.

WA-2 WIRELESS SUBWOOFER KIT CAPABLE
The Klipsch WA-2 Wireless Subwoofer Kit (sold separately) allows high resolution wireless connectivity for easy placement anywhere in your room and optimizes output and low frequency response. Connect up to four WA-2 wireless kits to compatible Klipsch subwoofers in a single room for a completely wireless connection.

FLEXIBLE CONTROLS
Low Pass Crossover and Variable Phase control allows you to tune the subwoofer to your Klipsch speakers and to your room, establishing the ideal level of bass. Line Level / LFE RCA inputs ensure compatibility with home theater receivers.

USE INPUTS SIMULTANEOUSLY
Both the RCA and wireless inputs can be utilized, giving you the ability to use a single subwoofer with multiple system in the same room. For example, you can use the wireless input for your home theater set up and the RCA input for your 2-channel system, without needing to switch inputs when changing between systems.

1/2-WATT STANDBY MODE
Exceptional efficiency on or off. Meets global efficiency standards - reducing energy costs for the user.

ULTRA-DURABLE EBONY FINISH
Scratch resistant ebony finish looks like real wood and covers the entire cabinet.

DETAILED DESIGN
Shock-absorbing rubber feet, steel grille posts and a woven cloth grille give the SPL subwoofers a premium look and feel.

All specifications are subject to change without notice. ©2018 Klipsch Group, Inc. Klipsch and Tractrix are registered trademarks of Klipsch Group, Inc. A wholly-owned subsidiary of Voxx International Corporation.