

HTS, ECC
HTS (US)
HTS (EU/UK)
HTS (CA)
HTS(China)
ECCN (US)
Country of Origin
DIMS, WEIG
Product Color
Fitment Features
Dimensions of retail box
Weight of glasses alone (excluding box/accessories)
Weight of charging case alone (excluding box/accessori
Dimensions of product alone
Weight of boxed retail unit
Master carton quantity
Dimensions of master pack
Weight of master pack
Pallet quantities
Master cartons per pallet layer
Total # of layers of each pallet
Dimensions of pallet
Weight of pallet
KJ EDITION - DIMS
Individual unit box dimensions (1 piece)
Individual unit box weight (1 piece)
"1pk mastercarton" box dimensions in mm (1 piece)
"1pk mastercarton" box weight in kg (1 piece)
"1pk mastercarton" configuration, if applicable: is certified? Drop t
8pk Mastercarton dimensions
8pk Mastercarton weight
8pk Mastercarton's pcs/box
8pk Mastercarton: will each mastercarton have a "Masterbox ID" number, like h
8pk Mastercarton is certified? Drop test, stack test?
Pallet Dimensions
Pallet Weight
Pallet stack rendering example (with focus on labels posi
Pallet: picture/pdf of each label
MEMORY, CAM
Memory Storage
Camera
Sensors
Video capture / Resolution

Camera Framing / Resolution
Controls
Buttons
LEDs
Display
Lens material
Temple Arms material
Frame material
BATTERY

Glasses Battery type
Glasses Battery model #
Glasses Battery weight
Glasses Battery capacity
Glasses Battery cell qty
Battery operating voltage
Lithium content weight
Glasses Battery shape
Glasses Battery Charging Time (hours)
Glasses Battery Operating time (hours)
Glasses battery UL Certification #
Glasses Battery MSDS(Material Safety Data Sheet) code. (headset
IEC62133 for battery testing, IEC62368 for whole system t

CHARGING CASE
Charging case material
Charging case Battery type
Charging case Battery model #
Charging case Battery weight
Charging case Battery capacity
Charging case Battery cell qty
Charging case Battery operating voltage
Lithium content weight
Charging case Battery shape
Charging case Battery Charging Time (hours)
Charging case Battery Operating time (hours)
Charging case battery UL Certification #
Charging Connector Type (on Device)
Charging Voltage
Charging Case UN38.3 Lithium Battery(Cell) Test
Charging Case Battery MSDS(Material Safety Data Sheet) code. (head

DANGEROUS GOODS
Dangerous Goods Classification (case alone)
Dangerous Goods Classification (Glasses alone)
Dangerous Goods Classification (Glasses and Case)

[illegible]

ADDIT

[illegible]

N, COOC INFORMATION	
	9504.50.0000
	9504.50.0000
	9504.50.0010
	9504.50.0000
	5A992.c
	occurs in Taiwan: Glasses made in Taiwan; all ot
GHT, COLOR INFORMATION	
	Asadjustable temple tips
	186 x 77 x 73mm
	53.8g
es)	179.6g
	• Temple Length: 150 mm Hinge to Hinge: 12
	432.7 g
	8
	321 x 199 x 173 mm
	3.759 kg
	864
	18
	6
	1219*1016*1173 mm
	422.27 kg
, WEIGHT, COLOR INFORMATION	
	186 x 88 x 80 mm
	.5328 kg (532.8g)
	202 x 115 x 149 mm
	0.751 kg
test, stack test?	Yes
	419 x 245 x 322 mm
	6.5 kg
	8 units
appening already for MRBD?	Yes
	ired per RL standards - ISTA 3A Drop Test, Stack
	1219 x 1016 x 1098 mm
	211 kg
tion)	KJ 1pk & 8pk MC proposal 04.pc
	KJ 1pk & 8pk MC proposal 04.pc
MERA, DISPLAY INFORMATION	
	1000+ photos
	~21.5mm) Diagonal FOV: 100 degree
	(Ambient Light Sensors) - TSL2521 (right arm), Ha
	1440 x 1920 pixels at 30 fps (4MP device output)

	3024 x 4032 pixels
	(Slider) Power on Hard Reboot
	Capture/Shutter and the rear function being
	2.4mm obround user LED (located at side
	N/A
	lens)
	TR XT 4546
	1st shot Injected TR XT 4546, 2nd shot Inject

BATTERY INFORMATION

	Large battery in the right temple	Small battery in
	Rechargeable-Lithium ion	Rechargeable
	MC-1444206A-B1	MC-1444
	4.14±0.15g	1.75±
	162 mAh/0.631 Wh	54mAh/C
	1	1
	4.48V	4.4
	0.0689g	0.02
	Rectangle	Recta
	Time to 96% 75 mins (shown as 100% in	
	Moderate user will have a 10 hrs runti	
	MH47612	MH4
& controller)	mez-f/view?usp=drive link	
esting	9qbQ6HZkCuU	

ASE BATTERY INFORMATION

	Olive- PU-Polyurathane
	Rechargeable-Lithium ion
	MC-1668047A-B
	23.5±0.5g
	1686mAh/6.53Wh
	1
	3.0 - 4.45V
	1.02g
	Rectangle
	0.59 hour) with a 15W adapter0% to 100% full charg
	glasses with up to 8 hours with single charge, up to
	UL-US-26103021-0
	USB-C
	4.45V
	Meta Platforms-Technologies-UN-38.3-Test-S
iset & controller)	DSY Bora Battery MSDS - 2026

US GOODS INFORMATION

	UN3480, Lithium-ion batteries, Class
	UN3481, Lithium-ion batteries contained in equi
	UN3481, Lithium-ion batteries packed with equi

ADDITIONAL QUESTIONS

[illegible]

ther products	
9 mm Lens	Adventurer
< Test (max 2 pa	
f	
f	
es	
ll Sensor (right	
t resolution)	

Al/Action	
e right)	
ed BTR800	
n the left temple	
-Lithium ion	
851A-B1	
0.15g	
0.211 Wh	
L	
8V	
94g	
angle	
MWA)	
ime.	
7612	
ge: Less than 116	
o 40 hours with f	
Summary-Bora	
s 9	
pment, Class 9	
pment, Class 9	

[illegible]

[illegible]