# Kodak PIXPRO Digital Devices

### SL5 SMART LENS® CAMERA

#### FEATURES:

Your smart phone just got a whole lot better. Introducing the new KODAK PIXPRO SL5 SMART LENS® camera. 5x mega zoom, built-in flash, and easy to attach to your smart phone for better looking photos and videos. And if that wasn't enough, the SL5 is wireless so you have even more flexibility to use it with or without your phone and upload your favorite shots to your social media streams. KODAK PIXPRO Digital Cameras - Tell your story.



- 16MP BSI CMOS sensor
- 5X Optical Zoom
- 28mm Wide Angle
- Full HD 1080p Video
- 6fps Burst Shooting
- Wi-Fi / NFC Compatible
- Wirelessly Connect / Control with Smart Devices







Available Colors:

Wireless









# Kodak PIXPRO SL5

Digital Device

16MP CMOS







Lithium-ion BATTERY

SPECIFICATIONS	SL5
Effective Image Sensor Pixels	16.35 Megapixels
Total Image Sensor Pixels	16.76 Megapixels [1/2.3" BSI CMOS]
Lens	
Focal Length	5.1 mm (Wide) – 25.5 mm (Tele)
[ 35mm film equivalent ]	[28 mm (Wide) – 140 mm (Tele)]
F number Lens Construction	F3.9 (Wide) — F6.3 (Tele)
Optical Zoom	8 groups 8 elements 5x
Focusing Range	ox Normal: (Wide) 60cm — ∞, (Tele) 100 cm — ∞
Focusing Range	Macro: 5 cm $-\infty$ (Wide Only)
Autofocus System	TTL Autofocus
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie File Format	1920x1080-30fps, 1280x720-30fps; High-Speed Movie: 848x480-120 fps
Still Image	Exif 2.3 (JPEG)
Movie	EXII 2.3 (JPEG) MP4 [Image: H.264; Audio:AAC (Monaural)]
Shooting Modes	P, ASCN, Burst Shooting, Low Light (WDR)
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Touch
Exposure Metering Method	Artificial Intelligence AE (AiAE)
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	<u>+</u> 3EV in 1/3 Step Increments
Shutter	Mechanical Shutter and Electronic Shutter
Type Speed	1/2000 - 4 Seconds
Continuous Shooting	Approx. 6fps (Full Resolution)
White Balance Control	Auto (AWB), Daylight, Cloudy, Flourescent, Flourescent CWF, Incandescent
Flash	
Flash Method	Internal
Flash Modes	Auto, Fill Flash, Foreced Off (Wide) Approv. 0.7m - 2.5m (ISO200); (Tale) Approv. 0.5m - 1.5m (ISO200)
Shooting Range Recording Media	(Wide) Approx. 0.3m - 2.5m (ISO800); (Tele) Approx. 0.5m - 1.5m (ISO800) Micro SD/Micro SDHC Card (Min. 4GB up to 32GB Max. Support) [MMC Card Not Supported]
Jacks	USB 2.0 (Micro 5 pin USB)
Wi-Fi	Yes (802.11 b/g/n)
NFC	Yes
Remote Control	Yes (via Smartphone)
Power	Rechargeable Li-ion Battery LB-012, 3.7V 700mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 160 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 8° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 2.15 x 2.15 x 1.68 in /54.8 x 54.8 x 42.9 mm (Based on CIPA Standards)
Weight	Approx. 4.30 oz. / 122 g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, AC Adapter, Wrist Strap, USB Cable, Quick Start Guide, User Manual, Service Card, Warranty Card
Compatible Devices	iPhone® 4/4s/5/5c/5s (iOS 6.0 and up) iPad® 1st - 4th generation (iOS 6.0 and up) iPod Touch® 4th generation (iOS 6.0 and up) Android® phones (version 2.3 and up) Android® tablets (version 3.0 and up)

### JK Imaging Ltd.

JK Imaging, Ltd. 1411 W. 190th Street, Suite 550 Gardena, CA 90248 To learn more about KODAK PIXPRO Digital Cameras: visit: **www.kodakpixpro.com** 



© 2015 JK Imaging, Ltd. The Kodak trademark and trade dress are used under license from Kodak. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0036.0121.en.02

