



Rugged, High-Performance Drive

With data transfer rates up to 1050MB/s read, 1000MB/s write¹, the Lexar® E6P Portable SSD offers the performance you need in a robust, ready-for-anything design that also provides essential heat dissipation. It is conveniently plug-and-play so there is no need for an additional power source or drivers.

Powerful Performance. With its USB 3.2 Gen 2 high-speed interface, the Lexar® E6P Portable SSD delivers data transfer rates up to 1050MB/s read, 1000MB/s write¹.

Built to Travel. The Lexar® E6P Portable SSD features an ultra-slim and sturdy design that makes it both easy to take with you and helps protect the drive.

Keeps its Cool. A premium aluminum enclosure offers exceptional heat dissipation, ensuring the drive doesn't overheat.

Sturdy and Safe. A rugged bumper surrounds the drive for added protection on the go.

Designed for Convenience. The Lexar® E6P Portable SSD includes a Type-C to Type-C and Type-C to USB-A cables and a lanyard plus it is entirely plug-and-play – no additional power or drivers required.

Rigorously tested. All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 25 years, Lexar has been trusted as a leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives, and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

Product Highlights:

- USB 3.2 Gen 2 high-speed interface with data transfer rates up to 1050MB/s read, 1000MB/s write¹
- Ultra-slim and sturdy design for portability and endurance
- Premium aluminum enclosure for exceptional heat dissipation
- Rugged bumper for added protection on the go
- Includes Type-C to Type-C and Type-C to USB-A cables and a lanyard
- Plug-and-play design – no additional power or drivers required

Capacities:

2TB
Up to 1050MB/s read, 1000MB/s write¹

1TB
Up to 1050MB/s read, 1000MB/s write¹



Lexar Retail Sku	Capacity	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LP AE06N001T-RNBNG	1TB	Global	843367132508	30843367132509	20
LP AE06N002T-RNBNG	2TB		843367132515	30843367132516	

¹Up to 1050MB/s read and 1000MB/s write speeds. Speeds based on internal testing. Actual performance may vary.

Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

Lexar is not liable for any loss of data or images.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

www.lexar.com

©2023 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Specifications

Capacity	1TB, 2TB
Interface	USB 3.2 Gen 2
Speed	up to 1050MB/s read, up to 1000MB/s write ¹
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Module Size	109 x 36 x 10 mm (4.291" x 1.417" x 0.394")
Warranty	2-year limited warranty

www.lexar.com

©2023 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.