



REF. GESLITSDWHF



REF. GESLITSDBKF

# BIENVENUE CHEZ GOGUETTE



At Goguette, we are committed to making your choice of wine fridge easier with a clear offering and quality wine fridge. Products with a unique design that seamlessly integrates into your home and respect the French wine tradition.



TEMPÉRATURE  
MAÎTRISÉE



RANGEMENT  
ADAPTE

MADE  
IN  
FRANCE  
WITH LOVE



VIBRATIONS  
LIMITÉES



PROTECTION  
CONTRE LA  
LUMIERE

35 dB(A)  
SILENCIEUSE

## Compatible accessories



Premium shelf



Presentation shelf



Shelf front



### Standard shelf

- Designed to store all kind and size of bottles
- Two possible use : storing to optimise your wine fridge capacity or sliding to an easy access to your bottles and protect the labels
- Different way to present your bottles.

# ENTRY LEVEL - LARGE SIZE - WINE STORAGE FRIDGE

Goguette



## GENERAL

|                |  |
|----------------|--|
| Installation   | Stand Alone                                    |
| Built-in       | Yes - according to the built-in specifications |
| Functionnality | Storing and serving                            |
| Origin         | Made in France                                 |
| Warranty       | 5 years  |
| Type of door   | Solid door                                     |

## INTERIOR LAYOUT

|                             |  |
|-----------------------------|--|
| Number of shelves           | 5  |
| Interior layout description | Optimised the storing capacity of the wine cabinet |
| Shelves use                 | 5 storing shelves                                  |
| Initial capacity            | 225  |

## SETTING AND PERFORMANCES

|                              |   |
|------------------------------|---|
| Control panel                | Aluminium<br>Possible to write on it with a chalk |
| Electronic regulation        | LCD touch screen                                  |
| Temperature display          | Yes, real temperature                             |
| Temperature setting range    | From 5°C to 18°C<br>with constant steps of 1°C    |
| Default temperature setpoint | 12°C  |
| Unit température setting     | Celsius or Fahrenheit                             |
| Lighting                     | No  |
| Sleeping mode                | Automatic or Off or manual triggering             |

## FUNCTIONALITY AND SRTUCTURE

|                 |                                      |
|-----------------|--------------------------------------|
| Useful volume   | 405 L                                |
| Adjustable feet | 2, at the front                      |
| Cold production | static with air ventilation          |
| Gaz used        | R600a                                |
| Compressor      | Variable speed (inverter technology) |

## LOGISTIC

|  |                          |
|--|--------------------------|
| acked product dimensions                             | H 1950 x W 720 x D 760mm |
| Product dimensions with the handle and the separator | H 1825 x W 680 x D 775mm |
| Product dimensions no handle, with the separatorée   | H 1825 x W 680 x D 725mm |

|               |  |
|---------------|--|
| Door material | Aluminium frame, plastic door angles, and aluminium handle                       |
| Color         | White, black angles and handle<br>Black, stainless steel color angles and handle |
| Reversibility | Yes  |

|                                       |   |
|---------------------------------------|---|
| Maximum fridge capacity               | 225   |
| Interior layout for maximal capacity  | 5 shelves   |
| Maximum weight supported by the shelf | 62,5 kg (4 ranks of bottles)                            |
| Shelf material                        | beech wood frame and recycled plastic bottles supportse |

|                               |                              |
|-------------------------------|------------------------------|
| Alarmes                       | Oui, visuelles               |
| Alarms                        | Yes, visual                  |
| Type of alarms                | temperature and sensor fault |
| Ambient operating temperature | From 0°C to 35°C             |
| Climate class                 | SN-T                         |
| Winter mode                   | Automatic                    |
| Energy consumption class      | D                            |
| Annual energy consumption     | 84 kWh/y                     |
| Sound emission level          | 35 dB(A)                     |

|                           |                                     |
|---------------------------|-------------------------------------|
| Heat release              | Heater                              |
| Inner material            | Aluminium                           |
| Exterior coating material | Hight pressure laminates panels HPL |
| Insulation type           | polyurethane foam (59mm)            |
| Cords                     | CE/ UK /CH                          |

|                        |         |
|------------------------|---------|
| Packed product weight  | 98,9 kg |
| Equiped product weight | 83,7 kg |
| Empty product weight   | 74,7 kg |