

## Spécifications techniques

Product Name	Dualtron Mini Special			Note
Motor	MAX 1450W BLDC HUB MOTOR			
Battery type	LG Li-ion battery	LG Li-ion battery	China Li-ion battery	
Battery capacity	52V21Ah	52V17.5Ah	52V13Ah	
Product weight	Around 23.9kg			Battery included weight
Charging time(1.7A)	12 hr+	10 hr+	7.6 hr+	When using standard charger(1.7A)
Charging time(6.5A)	3 hr+	2.6 hr+	2 hr+	When using quick charger(6.5A)
Max mileage	65km	55km	40km	75kg load,25km/h flat road continuous riding basis
Max speed	25 km/h			Speed adjustment function on the display.Single,Dual mode selection on the handlebar.
Folding	Handle on touch quick folding			
Gradeability	Around 37%(20°)			Weight,road condition,battery status,temperature can affect the gradeability
Max load	100kg			
Unfolding size	1115 x 600 x 1170 mm			Length x Width x Height
folding size	1110 x 205 x 410 mm			Length x Width x Height
Instrument panel	EYE throttle is applied as the default option.Battery level,TRIP,ODO,Time,Speed display and mode change.Start method.Cruise system,Slow start,Speed limit. Battery save Electric brake,ABS,LCD brightness control.Auto off time setting.			
Light	Handle sides LED lights,Dual LED head light & tail light,brake light			DC to DC converter is built in (12V 3A output)
Brake	Rear Drum brake + Electric ABS			
Suspension	Front & rear spring and rubber suspension			
Tire	9 inch x 2 wide tube tire(Air pressure Max 50PSI)			
Product material	Frame and handle:Aviation aluminum forging alloy,6082-T6,Shaft:SCM440, Covers:Polypropylene			