

Pioneer Dj



DIRECT DRIVE / RCA AND LINE OUTPUT / USB OUTPUT /  
EASY RECORDING TO COMPUTER / PROFESSIONAL LAYOUT /  
HIGH-QUALITY WARM SOUND / HIGH TORQUE / REKORDBOX  
DVS COMPATIBLE / DUST COVER WITH SLEEVE STAND /  
INCLUDES CARTRIDGE, STYLUS AND SLIPMAT

**PLX-500**

**VINYL REVOLUTION**



## PLX-500 | DIRECT DRIVE TURNTABLE

### DJ, SCRATCH AND LISTEN TO YOUR VINYL, PLUS RECORD IT TO DIGITAL FILES

PRODUCT FEATURES		MAIN SPECIFICATIONS		TONE ARM	
<p><b>Direct drive, high torque</b> DJ and scratch with confidence</p> <p><b>Professional layout</b> Inherits design traits from the PLX-1000 professional turntable</p> <p><b>USB output</b> Easily record your vinyl to high-quality digital files on your computer using the free rekordbox software</p> <p><b>Accessories included</b> Cartridge, stylus and slipmat all come in the box</p>	<p><b>High-quality audio</b> Enjoy warm analogue sound</p> <p><b>Phono and line output</b> Connect to your speakers without the need for an external amp</p> <p><b>Dust cover with sleeve stand</b> Display your record sleeves when the dust cover is open</p> <p><b>rekordbox dvs compatible</b> Use Control Vinyl, rekordbox dj and rekordbox dvs Plus Packs for dvs control</p>	<p><b>Power requirements</b> AC 100 V, 50 Hz/60 Hz</p> <p><b>Power consumption</b> 11 W</p> <p><b>Main unit weight</b> 10.7 kg</p> <p><b>Maximum dimensions (W x H x D)</b> 450 mm x 159 mm x 367 mm</p> <p><b>Output</b> RCA x 1, USB (type B)</p>	<p><b>Drive method</b> Servo type direct drive</p> <p><b>Motor</b> 3-phase brushless DC motor</p> <p><b>Braking system</b> Electronic brake</p> <p><b>Rotation speed</b> 33 1/3 rpm, 45 rpm, 78 rpm</p> <p><b>Rotation speed adjustment range</b> ±8%</p> <p><b>Wow and flutter</b> 0.5% or less WRMS</p> <p><b>S/N ratio</b> 50 dB or above</p> <p><b>Turntable</b> Aluminium die-casting Diameter: 332 mm</p> <p><b>Starting torque</b> 1.6 kg cm or more</p> <p><b>Start time</b> Within 1 second (at 33 1/3 rpm)</p> <p><b>Effective length</b> 230.5 mm</p>	<p><b>Arm type</b> Universal type S-shape tone arm, gimbal-supported type bearing structure, static balance type</p> <p><b>Overhang</b> 16 mm</p> <p><b>Tracking error</b> Within 3°</p> <p><b>Arm height adjustment range</b> 6 mm</p> <p><b>Stylus pressure variable range</b> 0 g to 4.0 g 1 scale 0.1 g</p> <p><b>Proper cartridge weight</b> 9.5 g or less (single cartridge)</p> <p><b>Cartridge type</b> VM type</p> <p><b>Included accessories</b> Slip mat, Dust cover with jacket stand, Adapter for EP record, Balance weight, Headshell (with cartridge), Shell weight, Power cord, USB cord, Audio conversion cord Stereo pin plug (female) – Stereo mini plug male)), Operating instructions</p>	
		<b>TURNTABLE</b>			
				<b>HEADSHELL SPECIFICATIONS</b>	
				<b>Weight</b>	10.0 g
				<b>Shell length</b>	52 mm
				<b>Finger Length</b>	21 mm
				<b>AVAILABLE IN WHITE</b>	

