TUF GAMING VG32AQL1A MONITOR



KEY FEATURES



WQHD crystal image quality with HDR effect 170 Hz
Rapid Refresh

High refresh rate for ultra fast and smooth gameplay



Enables ELMB together with VRR, eliminating ghosting and tearing for sharp gaming visuals



VESA DisplayHDR 400 certified to reproduce lifelike images



Fast IPS enables a 1ms response time (GTG) for sharp gaming visuals with high frame rates



To enhance the details in dark scenes



Support wide color gamut to reproduce vivid color



Eliminates smearing and tearing, allowing you to smoothly react to your game



With Low Input Lag, you can hit that target just in time



TUF Gaming VG32AQL1A has undergone stringent performance tests and is certified Flicker-free and Low Blue Light (Hardware solution) by TÜV Rheinland laboratories, a global provider of technical, safety, and certification services.



TUF GAMING VG32AQL1A MONITOR

| 101 | | DENCE IN MONITOR |
|-------------------|--|--|
| | Panel Size (diagonal) | 31.5" Wide Screen (16:9) |
| Display | Display Viewing Area | 698.112x392.688 mm |
| | Panel Backlight/ Type | WLED / Fast IPS |
| | Display Surface | Non-glare |
| | True Resolution | 2560 x 1440 |
| | Pixel Pitch | 0.273mm |
| | Brightness (typical) | 350 cd/m2 |
| | Brightness (HDR, Peak) | 400 cd/m2 |
| | Contrast Ratio (Max.) | 1,000:1 |
| | Viewing Angle (CR≧10) | 178°(H) / 178°(V) |
| | Color saturation | 99% DCI-P3 |
| | Display Colors | 16.7M |
| | Response Time | 1ms GTG |
| | Refresh rate | 170Hz (OC) |
| | Flicker Free | Yes |
| | HDR | DisplayHDR 400 |
| | Multiple HDR mode | Yes |
| Video Features | ELMB Sync | Yes |
| | HDCP | Yes |
| | GameVisual | Yes (FPS,RTS/RPG, Racing , sRGB, Cinema, Scenery, MOBA) |
| | GamePlus | Yes (Crosshair, Timer, FPS Counter, Display Alignment, Sniper) |
| | GameFast Input technology | Yes |
| | Low Blue Light | Yes, Hardware solution |
| Input / Output | | 2 x HDMI (v2.0) 1 x DisplayPort 1.2 3.5 mm earphone-jack, USB hub x2 |
| Speaker | Mark and fine | 2W x 2 stereo, RMS |
| Signal Frequency | | HDMI: 30 KHz ~223 KHz (H)/ 48 Hz~144 Hz (V) DP: 223KHz ~223 KHz (H)/ 48 Hz ~144 Hz (V) (non-OC) DP: 249KHz~249KHz (H)/ 48Hz~170Hz (V) (OC) |
| Power | Power Consumption | <27.1W* |
| | Voltage | 100-240V, 50 / 60 Hz |
| Mechanical Design | Tilt | +20°~ -5° |
| | Swivel | +10°~-10° |
| | Height adjustment | 0~90mm |
| Dimension | Phy. Dimension | 716 x (475~565) x 240mm (with stand) 716 x 426 x 54mm (without stand) 818 x 645 x 260mm (box) |
| Weight | 8.6 kg (net), 6.2 kg (net without stand),12.4 kg (gross) | |
| Special Features | Dynamic Shadow Boost, ELMB SYNC, G-Sync compatible, FreeSync Premium, 1ms GTG, DisplayWidget Lite | |
| Accessories | Power cord, Power adapter, Warranty card , QSG, HDMI cable(option), DP cable(option), USB cable (option) | |
| | | |

^{*1}ms GTG spec is based on internal testes. Response time may vary depending on test conditions ** measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection