

ProArt Display PA328QV



Key Features



WQHD
2560x1440

Supporting WQHD 2560x1440 resolution for crystal clear image quality



IPS technology is optimized for the finest image quality with 178° wide-viewing-angle



International color standard 100% sRGB / 100% Rec. 709 color space for digital images and video production



Factory pre-calibrated with ASUS advanced gray-scale tracking technology to guarantee the ΔE color difference value is less than 2



ProArt Palette to adjust color parameters delivers all consistency and quickly adjust to see different color performance



Extensive connectivity with DisplayPort, HDMI, Audio in, Earphone jack



Frameless Design

Frameless panel design for an ideal multi display setup



USB Hub

Embedded USB ports for connecting mouse, keyboard, or other USB devices



4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel, pivot, and height adjustments

ASUS

ProArt Display PA328QV

Spec Sheet

Display	Panel Size : 31.5-inch (80.09cm) Wide Screen (16:9) Display Viewing Area(HxV) : 698.112 x 392.688 mm Display Surface : Non-Glare Panel Type : IPS Viewing Angle (CR≥10, H/V) : 178° / 178° Pixel Pitch : 0.272 mm Resolution : 2560x1440 Color Space (sRGB) : 100% Color Space (Rec. 709) : 100% Brightness (HDR, Peak) : 400 cd/m² / (Typ.) : 350cd/m² Contrast Ratio (Typ.) : 1000:1 Display Colors : 1073.7M (10 bit) Response Time : 5ms (GTG) Refresh Rate (Max) : 75Hz HDR (High Dynamic Range) Support : HDR-10 Flicker-free : Yes	
Video Feature	Trace Free Technology : Yes ProArt Preset : Standard / sRGB / Rec. 709 / DCI-P3 / HDR / Scenery / Reading / Rapid Rendering / User Mode 1 / User Mode 2 Color Temp. Selection : Yes (5 modes) Color Adjustment : 6-axis adjustment (R,G,B,C,M,Y) Gamma adjustment : Yes (Support Gamma 1.8/2.0/2.2/2.4/2.6) Color Accuracy : $\Delta E < 2$ ProArt Palette : Yes QuickFit Plus : Yes PIP / PBP Technology : Yes HDCP : Yes, 2.2 VRR Technology : Adaptive-Sync Low Blue Light : Yes	
Audio Feature	Speaker : Yes (2Wx2)	
IO ports	DisplayPort 1.2 x 1 HDMI(v2.0) x 2  Earphone Jack DisplayPort1.2	USB Hub : Yes (USB 3.2 Gen1 Type-A x 4) Earphone Jack : Yes
Signal Frequency	Digital Signal Frequency : HDMI : 27~112 KHz (H), 24~75 Hz (V) DisplayPort : 112~112 KHz (H), 48~75 Hz (V)	
Power Consumption	Power On (Typical): < 26.5W Power Saving Mode : < 0.5W ; Power Off Mode : 0W (Hard Switch) 100~240V, 50/60Hz	
Mechanical Design	Tilt : Yes (+23° ~ -5°) Swivel : Yes (+30° ~ -30°) Pivot : Yes (+90° ~ -90°)	Height Adjustment : 0~130mm VESA Wall Mounting : 100x100mm Kensington Lock : Yes
Dimensions (Est.)	Phys. Dimension with Stand (W x H x D) : 714.8 x (465.6 ~ 595.6) x 245.0 mm Phys. Dimension without Stand (W x H x D) : 714.8 x 422.2 x 67.33 mm Box Dimension (W x H x D) : 841 x 525 x 317 mm	
Weight (Est.)	Net Weight with Stand : 11.5 kg Net Weight without Stand : 7 kg Gross Weight : 14.6 kg	
Accessories	Power cord, HDMI cable (optional), DisplayPort cable (optional), USB cable (optional), Calibration Report, Quick Start Guide, Warranty Card, Welcome Card	
Compliance Standard	Energy Star®, FCC, UL/cUL, ICES-3, CB, CE, ErP, WEEE, TUV-GS, TUV-Ergo, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, e-Standby, PSB, TCO, RoHS, CEC, WHQL Windows 7/10/11, TÜV Flicker Free, TÜV Low Blue Light	

* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice

