TN-4D

Direct-drive Analog Turntable





Main Features

- Direct-drive 2-speed Turntable
- Newly Developed Low-profile Brush-less DC Motor exclusive for Direct-drive
- Sleek Cabinet Design that conventional Direct-drive Turntables never achieved
- Aluminium Die-cast Platter
- Static-balanced S-shaped Knife-edge Aluminum Tone-arm by SAEC
- Anti-skating Mechanism
- Universal Head-shell for quick cartridge replacement
- Built-in PHONO EQ Amplifier (MM type)
- PHONO/LINE Switchable Outputs with GND Terminal
- USB Output for Digital Recording on PC/Mac
- High-density MDF Cabinet for robust construction
- Detachable Dust Cover
- SUMIKO Oyster MM type Cartridge (factory instralled)
- Available in Piano Black and Walnut veneer finish

General Specifications

Drive Mechanism: Direct-drive • Turntable Speed: 33-1/3, 45 rpm

• Wow-flutter: 0.1%

S/N Ratio: 67dB or higher (A-weighted, 20kHz, LPF)

PHONO Output Level: 4.0mV (1kHz) LINE Output Level: 224mV (-13dBV)

● PHONO/LINE Output: RCA x 1 pair (switchable)

USB Output: USB B-type x 1 Digital Output Format: PCM 16-bit,

8/11.025/16/22.05/32/44.1/48kHz

Operation Power: AC 100-230V, 50/60Hz

Power Consumption: 2W or less (0.5W or less at Standby)

Dimensions (WxHxD): 16.5" x 4.6" x 14" 420 x 117 x 356 mm

(dust cover closed)

Weight: Approx. 13.5 lbs. / 6.1 kg





Knife-edge Tone-arm by SAEC