

AKZ9 9480 NB

12NC/Fx: 859991639410

GTIN (EAN) code: 8003437835858

DIMENSION	MEAS	URI
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mm
Space in front, which is required to install bottom trim	10	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	No	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm ²
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Minimum space for inbound ventilation (tall cabinet)	0	mm
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm ²
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm ²
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	_	
Minimum space for inbound ventilation (base cabinet)	0	mm
Minimum area for inbound ventilation cavity (base cabinet)	0	cm ²
BASE CABINET (vent-shaft outgoing)	- U	J
Indicates the position of the freespace for the outbound airflow (base cabinet)	_	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm ²
minimum area for eathering ventulation eavity (vase earlier)	U	Citi

Height of the front 595 mm Width of the front 595 mm Maximum depth all protruding elements, e.g. handles, controls 20 mm Maximum depth all protruding elements, e.g. handles, controls 41 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance in height is adjustable When product panel is missing, set to 0 product panel is missing area of appliances and lower handle product panel is missing area of appliances and lower handle product product panel is missing area of appliances and lower handle product product panel is missing area of appliances and lower handle product product product body product produc	DIMENSION		EASURE	
Width of the front 20 mm Maximum depth all protruding elements, e.g. handles, controls 20 mm Maximum depth all protruding elements, e.g. handles, controls 37 mm neighbour front more than 90 degrees 37 mm neighbour front more than 90 degrees 38 mm Projection of front in relation to housing of appliance 39 mm appliance, if height is adjustable 30 mm Space in front, which is required to guarantee full operability. The most protruding part gives this 30 mm Grontal handle thickness 30 mm Frontal handle thickness 30 mm Frontal handle thickness 572 mm MAX Height of the product body 572 mm More the product body 572 mm More the product body 574 mm Depth of the product body 575 mm Depth of product excluding protruding interface elements 564 mm	APPLIANCE			
Depth of the front Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width MIN Height of the product body MAX Height of the product body Depth of the product body 572 mm MAX Height of the product body 546 mm	Height of the front	595	mm	
Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width MIN Height of the product body MAX Height of the product body MAY Height of the product body 572 mm Width of the product body 546 mm Depth of the product excluding protruding interface elements - mm - mm - mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 346 mm	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width MIN Height of the product body MAX Height of the product body S72 mm Width of the product body S72 mm Width of the product body S46 mm Suppliance state as a special protruding interface elements S64 mm S64 mm S64 mm S64 mm S65 mm S66 mm S66 mm S66 mm S67 mm S6	Depth of the front	20	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance 18 mm Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable 97 mm Appliance, if height is required to guarantee full operability. The most protruding part gives this dimension 458 mm dimension 458 mm dimension 442 mm Appliance and lower handle 442 mm Appliance width 442 mm Appliance width 442 mm Appliance width 442 mm Appliance width 444 mm Appliance width 445 mm	Maximum depth all protruding elements, e.g. handles, controls	41	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle thickness Frontal handle width 521 mm MIN Height of the product body MAX Height of the product body 572 mm Width of the product body 574 mm Full depth of product excluding protruding interface elements - mm - mm - mm - mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	, , , , , , , , , , , , , , , , , , ,	37	mm	
appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width 521 mm MIN Height of the product body 572 mm Width of the product body 572 mm Width of the product body 574 mm Upepth of the product body 575 mm Full depth of product excluding protruding interface elements 564 mm	Projection of front in relation to housing of appliance	18	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width 521 mm MIN Height of the product body 572 mm Width of the product body 573 mm Width of the product body 574 mm Width of the product body 575 mm Full depth of product excluding protruding interface elements 564 mm mm mm mm mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Depth from front end of the niche to the front end of the freespace of the retrace 345 mm		5	mm	
dimension Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height for the product body Height of product excluding protruding interface elements Height of the product body Hei	When product panel is missing, set to 0	97	mm	
Frontal handle thickness 30 mm Frontal handle width 521 mm MIN Height of the product body 572 mm MAX Height of the product body 572 mm Width of the product body 572 mm Unit of the product body 574 mm Depth of the product body 574 mm Full depth of product excluding protruding interface elements 574 mm Full depth of product excluding protruding interface elements 574 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of product excluding protruding interface elements 575 mm Full depth of produ		458	mm	
Frontal handle width 521 mm MIN Height of the product body 572 mm MAX Height of the product body 572 mm Width of the product body 546 mm Depth of the product body 543 mm Full depth of product excluding protruding interface elements 564 mm - Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door 1 opened totally 1 opened 1 op	Height from bearing area of appliances and lower handle	442	mm	
MIN Height of the product body 572 mm MAX Height of the product body 572 mm Width of the product body 546 mm Depth of the product body 543 mm Full depth of product excluding protruding interface elements 564 mm mm mm mm mm mm mm Appliance Can be used as base for other appliances from the same manufacturer. Default is "No" No Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Appliance other 0 mm	Frontal handle thickness	30	mm	
MAX Height of the product body Width of the product body Depth of the product body Full depth of product excluding protruding interface elements - mm mm mm mm mm Appliance Can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Frontal handle width	521	mm	
Width of the product body Depth of the product body Full depth of product excluding protruding interface elements	MIN Height of the product body	572	mm	
Depth of the product body Full depth of product excluding protruding interface elements 564 mm	MAX Height of the product body	572	mm	
Full depth of product excluding protruding interface elements - mm - m	Width of the product body	546	mm	
- mm	Depth of the product body	543	mm	
- mm	Full depth of product excluding protruding interface elements	564	mm	
- mm	-	-	mm	
- mm		-	mm	
- mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace - mm - mm - mm - mm 0 mm 89 mm Appliance Side swing door Lateral projection of pened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm	-	-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace - mm Appliance In mm - mm Appliance other - mm 0 mm Appliance other of the niche to the front end of the freespace of the retrace		-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	-	-	mm	
Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm		-	mm	
Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Appliance Flap door			
Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Projection of the opened flap in relation to bearing area	0	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Maximum angle when flap door is opened totally	89	mm	
mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Appliance Side swing door			
Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm		0	mm	
Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 345 mm	Maximum angle when door is opened totally	0	mm	
·	Appliance other			
Height from niche to bottom end of freespace for the retrace 537 mm	Depth from front end of the niche to the front end of the freespace of the retrace	345	mm	
	Height from niche to bottom end of freespace for the retrace	537	mm	