




PF		
S	Falmec Lab	
M	Evo - Island - 35 cm - Copper - 800 m3/h	
AEC	57.6	kWh/a
EEC	A	
FDE	31.6	
FDEC	A	
LE	29.9	
LEC	A	
GFE	76	
GFEC	C	
Qmin	354	m ³ /h
Qmax	655	m ³ /h
Qboost	765	m ³ /h
SPEmin	48	dBa
SPEmax	65	dBa
SPEboost	69	dBa
PO		
PS	0	W
PI		
F	0	
EEl	53	
Qbep	449	m ³ /h
Pbep	411	Pa
Qboost	765	m ³ /h
Wbep	162	W
WL	6	W
Emiddle	179	lux
Lwa-SPEmax	65	dBa

PF_Scheda prodotto conforme a 65/2014 S_Vendor name / M_Project identification / AEC_Yearly energy consumption (AEC) hood / EEC_Energy efficiency class / FDE_Fluid dynamic efficiency (FDE) hood / FDEC_Fluid dynamic efficiency class / LE_Light efficiency (LE) hood / LEC_Light efficiency class of luminous efficiency / GFE_Fat filtration efficiency / GFEC_Fat filtration efficiency class / Qmin_Airflow (in m³/h) at minimum power under normal use conditions / Qmax_Airflow (in m³/h) at maximum power under normal use conditions / Qboost_Airflow (in m³/h) at the intensive power / SPEmin_A-weighted sound power of airborne noise emissions at the minimum power under normal use conditions / SPEmax_A-weighted sound power of airborne noise emissions at the maximum power under normal use conditions / SPEboost_A-weighted sound power of airborne noise emissions under intensive or boost use conditions / PO_CPower consumption in off mode (Pa) / Pa_CPower consumption in standby mode (Pa).

PI_Additional information in accordance with 66/2014 4 F_Factor of increase over time / EEl_Energy Efficiency Index / Qbep_Airflow speed measured at best efficiency point / Pbep_Air pressure measured at best efficiency point / Qboost_Full airflow / Wbep_Energy input measured at best efficiency point / WL_Nominal power of lighting system / Emiddle_Average illumination of lighting system on cooking surface / Lwa-SPEmax_Low pressure level at maximum power